


ZAS21523

1080P 4 in 1 IR High Speed dome Camera



Features

- Keep original analog system
- Real time transmission ,lossless video
- High definition 1080P, 23x Zoom
- Long distance transmission up to 500 meters
- OSD menu available/With 8pcs IR-Led.IR Range:150M
- 7" Total metal body construction,IP66 rate protection
- IR illumination&power consumption is variable dependant on zoom facto
- Optional alarm and audio



Technical Specification

Model	ZAS21523
Sensor	1/3" Sony 323 CMOS
Effective pixels	1080P 1920(H)X1080(V)
Total pixels	2.0MP
Lens	23X f=5.35mm~96.3mm
Iris	F1.6~F3.0
Min. illumination	Color: 0.5Lux \ B/W: 0.05Lux
BLC	Support
WB	Indoor/Outdoor/Auto/Manual
D/N	IR-CUT
S/N Ratio	≥50dB
WDR	DWDR

Technical Specification

Dome

DSP	NVP2441
Horizontal Rotation Speed	0.02 ~ 480°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	0.02 ~ 160°/s
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 93°
Ratio Speed	Support
Preset Points	220
Go to Preset Speed	1-64 grades setting available
360° Scan	User programmable
A-B Scan	User programmable
A-B Scan Speed	1-64 grades setting available
Dwell Preset	1-60s interval available
Guard Tours	8 groups
Guard Points	Max.16 points, dwell time user selectable
Pattern Scan	4 pcs
Pattern Scan Record	Max. 512 commands
OSD Menu	Multiple languages for OSD menu, English, Spanish, French, Italian etc.;
Time Scheduling Function	6 tasks
PWR on Action	Memory/Pattern 1/Tour 1/360 scan/AB scan/Preset 1-8/None
Signal Transfer	TVI/AHD/CVI/CVBS Selectable
Park Time	1-60mins setting available
Park Mode	Pattern 1/Tour 1/360 scan/AB scan/Preset 1-8/None
Pan and Tilt position display	Support
Baud Rate	1200/2400/4800/9600bps
Communication	RS485 /Coaxical cable
Alarm function	Support,4 in,2 out
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Power Supply	DC12V 4A
Power Consumption	≤25W
Lightning Protection	Transient voltage 6000V

IR parameters

Auto control IR LED	PWM
LEDs	Array 42Mil
IR distance	Up to 150 meters
IR illumination on	1-15 grades selectable